

All Purpose Cement

Heavy-bodied clear cement for use on ABS, PVC, and CPVC pipe and fittings up to 12" in diameter. Flows freely and provides a thick layer. Helps fill gaps in larger diameter pipe and joints.



- 112609 4 oz.; 24/Ctn.
- 112610 8 oz.; 24/Ctn.
- 112615 16 oz.; 24/Ctn.
- 112611 32 oz.; 12/Ctn.

FlowGuard Gold 1-Step CPVC Cement

Oatey's one-step cement for CPVC is specially formulated to bond with FlowGuard Gold CPVC where all-purpose cements will not. Needs no primer, faster cure time than regular cements, low VOC, meets ASTM D-2846 & F-4 93. Exceeds environmental requirements.



- 112630 4 oz.; 24/ctn
- 112631 8 oz.; 24/ctn

ABS-To-PVC Transition Green Cement

Medium-bodied green-colored cement for use in joining ABS to PVC in non-pressure transition joints. All schedules up to 6" dia. pipe and fittings. Recommended application temperature 40°F to 110°F. Meets ASTM D-3138.



- 112613 16 oz.; 6/ctn

NEW!

ABS Cement

Medium-bodied black cement for use on ABS pipe and fittings up to 6" in diameter. For all pressure and non-pressure applications.



- 112619 4 oz.; 24/Ctn.
- 112612 16 oz.; 24/Ctn.
- 112620 8 oz.; 24/Ctn.
- 112621 32 oz.; 12/Ctn.

Purple Primer/Cleaner

All purpose primer/cleaner for PVC/CPVC pipe and fittings. Purple tint tells you primer has been used. Removes surface dirt, grease and grime; also softens pipe surface to allow for a fast and permanent solvent weld. Flows freely, evaporates quickly.



- 112616 8 oz.; 24/ctn
- 112622 32 oz.; 12/ctn

Clear Cleaner

A clear cleaner recommended for use on ABS, PVC and CPVC pipe and fittings, all schedules and diameters. A fast-acting cleaner to remove surface dirt, grease and grime. Flows freely and evaporates quickly. Apply at temperatures 40°F to 100°F.



- 112640 8 oz.; 24/ctn

Rain-R-Shine

Fast-setting blue PVC cement for solvent welding under damp or wet conditions; effective when quick pressurization is needed. Ideal for sprinkler or pool installations.



- 112607 16 oz.; 24/Ctn.

PVC Cement

Regular-bodied clear cement for PVC pipe and fittings up to 3" dia. Use on Schedule 40 and Schedule 80 potable water pressure pipe, gas, conduit, drain waste and vent pipe. Flows freely, sets-up quickly. Apply at temperatures 40° - 90° F. NSF and UPC approved. Exceeds ASTM D-2564.



- 112614 4 oz.; 24/ctn

Cold Weather Cement

Medium bodied clear cement for use on PVC pipe and fittings up to 6" dia. Formulated for fast initial set up at temperatures down to -5° F to 100° F Sch. 40 and Sch. 80. Non-pressure, DWV, up through 4" diameter, no primer needed where local codes permit. Recommended for all grades and types of PVC pipe and fittings, potable water, pressure pipe, gas, conduit and DWV. Meets ASTM D-2564.



- 112625 Pint; 24/ctn

Pipe Joint Compound

Non-toxic, fast-set, non-hardening paste lubricates and seals threaded joints. Use on water, natural gas, steam and air lines.



- 112801 2 oz. Tube; 12/ctn
- 112901 4 oz. with Brush; 12/ctn

Blevins Order Online Anytime at www.blevinsinc.com